

TRANSPORTABLE FUEL STORAGE



OST-SERIES **TANKS**

*Self-Bunded Bulk
Fuel Storage Tanks*



1000 - 6000 LITRES

OST-SERIES TANKS

G Gasoline

S Solvents

L Lubricants

D Diesel

Orca Fuel Solutions' OST tanks are the best solution for the storage and dispensing of diesel, gasoline and lubricant oils from 1000 - 6000 litres.

They offer a flexible solution for storing combustible liquids while improving fuel dispensing and management. Their practical design ensures fast, easy, and convenient installation in any location, indoors or outdoors.

OST-SERIES TANKS OFFER A FAST, EASY AND CONVENIENT HYDROCARBON STORAGE SOLUTION.

These mobile and modular units ensure fast, easy transportation to site, are easily relocatable, and require minimal site preparation. Their place-fill-and-pump installation process delivers versatility and rapid commissioning on site.

The freestanding design provides complete 360° access for tank viewing and inspections.

The curved rooftop design and high-grade paint finish ensures enhanced durability in harsh environments.

DOUBLE-WALL CONTAINMENT FOR ADDED SAFETY AND SECURITY.

Our double-walled tanks are designed as integral secondary containment and therefore do not require independent bunds for leak containment. Double-walled tank = SFL primary tank + interstitial space + secondary external tank.



STANDARD FEATURES

- Meets UL-142 and ULC-S601-14 compliance as standard
- Double-walled tank construction consists of a 5mm primary steel tank and a 3mm secondary steel tank
- Baffled internally to reduce product movement should the unit be moved with contents.*
- Accessible and removable tank manway for internal tank maintenance and cleaning.
- Recessed spill box/pump cabinet with pump mounting bracket. All housed under heavy duty lockable lid for additional fuel security.
- Sectional cut-outs on sides of spill box to allow flexible hoses or pipework to external requirements (i.e: generators).
- Curved roof feature for water drainage to top of tank.*
- Complete with aluminium gauged dipsticks, 1 x galvanized updraft vent breather system and multiple port fittings.
- Air pressure tested prior to leaving our factory.
- Mobile and modular design allows for ease of transportation.
- 250-300 Micron thickness 'WHITE' paint finish as standard. Other colour options are available upon request.
- Flammable and combustible liquid safety labels and decals supplied as standard.
- Forklift pockets and certified tie down/lifting points at each corner.

**12 MONTH
PAINT
WARRANTY**



*Conditions apply. Some features standard, some optional extras, depending on product range. Custom colours, coatings, dimensions and refuelling equipment packages are available upon request.

OST-SERIES SPECIFICATIONS

Dimensions are nominal.
Alternative capacities available
upon request.

MODEL	SFL Litres	CAPACITY Litres	LENGTH mm	WIDTH mm	HEIGHT mm	TARE kg	PUMP BAY
OST-1000	1,000	1,160	1,864	1,100	1,309	872	Yes
OST-2000	1,890	2,000	2,274	1,416*	1,309	1,120	Yes
OST-2500	2,500	2,684	2,274	1,674*	1,309	1,270	Yes
OST-4500	4,500	4,800	2,774	2,274*	1,309	1,768	Yes
OST-6000	6,000	6,200	3,574	2,274*	1,309	2,800	Yes

Waste Oil, Aviation and Fireguard options available on OST TANKS. Check with ORCA FUEL SOLUTIONS on specifications.

*Additional bolt-on double-walled pump bays available on request.



MANWAY (INSIDE LID)

- 1 x 2" Fill Point
- 1 x 2" Dip Point
- 2 x 2" Suction Ports (BSP & NPT)
- 2 x 2" Return Ports (BSP & NPT)
- 2 x 1" Suction Ports (BSP & NPT)
- 2 x 1" Return Ports (BSP & NPT)

MOBILE AND MODULAR

- OST- 1000 to 6000: Forklift pockets designed into base.
- Tie down/lifting points located at each corner.
- Tanks can be stacked four high empty, and two high full to maximise storage space.

EXTERIOR OF TANK

- 1 x 2" Interstitial Dip / Vent
- 1 x 2" Suction Port (BSP)
- 1 x 2" Spare Port
- 2 x 4" Submersible Pump Provision (BSP & NPT)
- 1 x 2" Free Vent Port